

# PowerCommand® LonWorks® Gateway (FT-10)



#### **Description**

The PowerCommand LonWorks Gateway provides local or remote access from a network installation to a personal computer. The LONWORKS Gateway allows software applications to use the EIA-232 port of a personal computer (PC) to gain access to the network. When used in conjunction with a Hayes<sup>®</sup> compatible modem, the LONWORKS Gateway allows remote access to the network through existing phone lines.

The LonWorks Gateway provides all necessary modem support for automatic dialout of fault conditions and remote access to the network. Network security is also provided via a programmable user-defined password.

#### **Features**

- Provides personal computers with local or remote access to a PowerCommand Network.
- Password protection prevents unauthorized access to the PowerCommand Network.
- Supports all Hayes compatible modems.
- Backwards compatible with all original equipment.
- Metal enclosure meets FCC class B & VDE level B requirements.
- Includes network terminator, wall mount power supply, serial cables and wall mounting brackets.

### **Specifications**

**Communications** 

Network: LonWorks FT-10 Serial:

EIA-232 38,400 bps (DCE)

**Dimensions** 

Size: 5.4 x 4.0 x 1.3 in

(13.8 x 10.2 x 3.4 cm)

Certified

Safety: UL, TuV

EMI: FCC, EU Class B Power\*

9 - 30 VAC or DC Voltage: 250 mA (typical) Current:

**Temperature** 


Operating: -40 to +185°F (-40 to +85°C) -40 to +185°F (-40 to +85°C) Storage:

**Humidity** 

Operating: 25 - 95% RH (non-condensing)

Power is provided by appropriate wall mount power supply.

#### **Typical Installation**



## **Ordering Information**

Part Number	Description	Input Volts / Hz	Plug Type
0541-0866-01	PowerCommand LonWorks Gateway Kit (US)	DC	
0541-0866-02	PowerCommand LonWorks Gateway Kit (US)	120 VAC / 60 Hz	NEMA 1-15P
0541-0866-03	PowerCommand LonWorks Gateway Kit (Europe)	230 VAC / 60 Hz	(2-prong)
0541-0866-04		230 VAC / 50 Hz	(3-prong)
0541-0866-05	PowerCommand LonWorks Gateway Kit (Japan)	100 VAC / 50,60 Hz	NEMA 1-15P

## See your distributor for more information



Cummins Power Generation 1400 73rd Avenue N.E. Minneapolis, MN 55432 763.574.5000 Fax: 763.574.5298 www.cumminspower.com

Cummins Power Generation is a subsidiary of Cummins Inc. PowerCommand is a registered trademark of Cummins Inc. LonWorks is a registered trademark of Echelon. Hayes trademark is a division of Zoom Telephonics, Inc.

**AWARNING** For Professional Use Only. Must be installed by a qualified service technician. Improper installation presents hazards of electrical shock and improper operation, resulting in severe personal injury and/or property damage.

**AWARNING** Back feed to a utility system can cause electrocution and/or property damage. Do not connect generator sets to any building electrical system except through an approved device or after building main switch is open.